

# TRUE-SURFACE® VIBE V™ VIBRATORY GREENS ROLLER



## Specifications

<b>Weight:</b>	Average of 85 lbs per unit
<b>Frame:</b>	One piece welded assembly, formed steel frame
<b>Roller Tube:</b>	5.5" O.D. tube, .188" wall, 22.5" roller length 1018 mild steel
<b>Roller Hub:</b>	(2) Relubricatable flange mounted bushings 1.5" I.D.
<b>Roller Shaft:</b>	1" diameter 1045 mild steel, drilled and tapped for eccentric weights
<b>Shaft bearings:</b>	Shielded type, maintenance free ball bearings.
<b>Shaft Eccentric Speed:</b>	Designed to run at your greensmower's maximum RPM speed.
<b>Front Roller:</b>	22.25" roller length, 2.5" diameter, stainless steel roller
<b>Patented:</b>	US Patent No. 5,261,213



### Attaches Directly To Triplex Greens Mowers:

- Toro GM3-3150, Toro 3200, Toro 3250 & Toro TriFlex 3300
- Jacobsen Greensking 3, 4, 5, 6 & Jacobsen E322
- Jacobsen GPlex I, II, III & GP 400
- John Deere 2243, 2500, 2500E, & QA5
- Ransome

### Selectable Vibration Settings

Select the amount of vibration you want to release into your greens with the patented Select-A-Vibe™ Dial. The Vibe V™ is the only golf course greens roller equipped with a dial allowing you to adjust your vibration level – giving you complete control of your greens. With 5 settings, you can select the EXACT vibration needed for your application to custom fit your greens:

1. Establishing new greens
2. Regular greens rolling – at least every other day
3. Vibrating-in topdressing
4. Truing greens after aerification
5. Tournament preparation rolling

**1-800-443-8506**  
**www.true-surface.com**

**TRUE-SURFACE®**   
**... makes true greens!™**